

Agricultural telehandlers on the UK market - 2018

Here's our guide to agricultural telescopic handlers on offer in the UK. In the 'Hydraulics' column: F = Fixed output gear pump; V = Variable flow demand-responsive piston pump and valving; litres/min. 'Engine' column: power and engine make. 'Transmission' columns: 1spd = continuous drive from zero to top speed; hydro - single motor hydrostatic drive; x2 hydro - twin motor hydrostatic drive; 2/3spd - number of hydrostatic drive ranges (by flow management or gearbox) or number of manual or powershift gears with torque converter.

Model	Max lift capacity	Max lift full height	Boom cushion	Hydraulics - litres/min	Engine - output; make	Transmission - gears and drive	Transmission - top speed
Avant							
Central cab, articulated chassis steering							
320S	0.65t	0.65t / 2.40m	no	F 45	20hp Kubota	1spd hydro	9km/hr
320S+	0.65t	0.65t / 2.40m	no	F 45	20hp Kubota	1spd hydro	9km/hr
420	0.65t	0.65t / 2.75m	no	F 31	20hp Kubota	1spd hydro	12km/hr
423	0.65t	0.65t / 2.75m	no	F 43	22hp Kubota	1spd hydro	12km/hr
520	0.80t	0.80t / 2.79m	no	F 31	20hp Kubota	1spd hydro	12km/hr
523	0.80t	0.80t / 2.79m	no	F 34	22hp Kubota	1spd hydro	12km/hr
525 LPG	0.80t	0.80t / 2.79m	no	F 36	23hp Kubota	1spd hydro	12km/hr
e5	0.90t	0.90t / 2.79m	no	F 30	201Ah battery	2spd hydro	10km/hr
528	0.95t	0.95t / 2.79m	no	F 36	28hp Kubota	1spd hydro	12km/hr
530	0.95t	0.95t / 2.79m	no	F 36	26hp Kubota	2spd hydro	19km/hr
e6	0.90t	0.90t / 2.83m	no	F 30	288Ah Li battery	2spd hydro	10km/hr
630	1.10t	1.10t / 2.83m	no	F 44	28hp Kubota	1spd hydro	14km/hr
635	1.10t	1.10t / 2.83m	no	F 66	37hp Kubota	1spd hydro	14km/hr
640	1.10t	1.10t / 2.83m	no	F 66	37hp Kubota	2spd hydro	22km/hr
745	1.40t	1.40t / 2.99m	no	F 70	49hp Kubota	1spd hydro	15km/hr
750	1.40t	1.40t / 3.08m	std	F 70	49hp Kubota	2spd hydro	25km/hr
755i	1.40t	1.40t / 3.10m	no	F 80	57hp Kohler	1spd hydro	17km/hr
760i	1.40t	1.40t / 3.10m	std	F 80	57hp Kohler	2spd hydro	30km/hr
<i>Note: Optional cab available on 400-700 Series; 500-700 Series have attachment self-levelling.</i>							
Blaney							
Central cab, articulated chassis steering							
TL1 10-33	1.00t	1.00t / 3.30m	opt	F 50	50hp Perkins	2spd hydro	na
Offset cab, permanent four-wheel steering							
TH1 15-48	1.50t	1.50t / 4.80m	opt	F 50	50hp Perkins	2spd hydro	na
Bobcat							
Offset cab, selectable two/four-wheel steering							
TL26.60	2.60t	2.00t / 5.89m	std	F 80	75hp Bobcat	2spd hydro	30km/hr
TL26.60	2.60t	2.00t / 5.89m	std	F 100	100hp Bobcat	2spd hydro	40km/hr
TL30.60	3.00t	2.50t / 5.89m	std	F 80	75hp Bobcat	2spd hydro	30km/hr

TL30.60	3.00t	2.50t / 5.89m	std	F 100	100hp Bobcat	2spd hydro	40km/hr
TL30.60 Agri	3.00t	2.50t / 5.89m	std	F 100	100hp Bobcat	2spd hydro	40km/hr
TL34.65 HF	3.40t	3.40t / 6.41m	std	V 190	130hp Bobcat	4spd hydro	40km/hr
TL34.65 HF Agri	3.40t	3.40t / 6.41m	std	V 190	130hp Bobcat	4spd hydro	40km/hr
TL30.70	3.00t	2.00t / 6.75m	std	F 100	75hp Bobcat	2spd hydro	40km/hr
TL30.70	3.00t	2.00t / 6.75m	std	F 100	100hp Bobcat	2spd hydro	40km/hr
TL30.70 Agri	3.00t	2.00t / 6.75m	std	F 100	100hp Bobcat	2spd hydro	40km/hr
TL38.70 HF	3.80t	3.50t / 6.97m	std	V 190	130hp Bobcat	4spd hydro	40km/hr
TL38.70 HF Agri	3.80t	3.50t / 6.97m	std	V 190	130hp Bobcat	4spd hydro	40km/hr
TL35.70	3.50t	3.50t / 6.97m	std	F 100	100hp Bobcat	4spd hydro	40km/hr
TL35.70 Agri	3.50t	3.50t / 6.97m	std	F 100	100hp Bobcat	4spd hydro	40km/hr

Note: TL Agri models have auto reversing engine fan, roof wiper, tow hitch and trailer braking valve, additional work lights, higher-spec 24in tyres, air seat, radio-ready and other cab equipment enhancements. TL26.60, TL30.60 and TL30.70 have choice of cab mounting positions for minimum height or maximum visibility. All models have independent engine and ground speed control; four-speed transmissions have two mechanical gears and two hydrostatic ranges. Bobcat engines built by parent company Doosan.

Case IH

Offset cab, selectable two/four-wheel steering

Farmlift 525	2.50t	2.50t / 5.78m	opt	F 80	74hp Kubota	1spd hydro	26km/hr
Farmlift 632	3.20t	3.20t / 6.10m	opt	F 120	133hp FPT	4spd p'shift	40km/hr
Farmlift 635	3.50t	3.50t / 6.10m	opt	V 140	146hp FPT	6spd p'shift	40km/hr
Farmlift 735	3.50t	2.50t / 7.00m	opt	F 120	133hp FPT	4spd p'shift	40km/hr
Farmlift 742	4.20t	2.50t / 7.00m	opt	V 140	146hp FPT	6spd p'shift	40km/hr
Farmlift 935	3.50t	1.50t / 9.10m	opt	F 120	133hp FPT	4spd p'shift	40km/hr

Caterpillar

Offset cab, selectable two/four-wheel steering

TH357D AG	3.50t	2.25t / 7.00m	std	V 150	111hp Cat	6spd p'shift	40km/hr
TH357D	3.50t	2.25t / 7.00m	std	V 150	124hp Cat	6spd p'shift	40km/hr
TH408D	4.00t	2.02t / 7.60m	std	V 150	111hp Cat	6spd p'shift	40km/hr
TH408D	4.00t	2.02t / 7.60m	std	V 150	124hp Cat	6spd p'shift	40km/hr
TH408D	4.00t	2.02t / 7.60m	std	V 150	142hp Cat	6spd p'shift	40km/hr
TH3510D AG Performance	3.50t	0.77t/9.80m	std	V 150	111hp Cat	6spd p'shift	40km/hr
TH3510D AG Performance	3.50t	0.77t/9.80m	std	V 150	124hp Cat	6spd p'shift	40km/hr
TH3510D AG Exclusive	3.50t	0.77t/9.80m	std	V 150	142hp Cat	6spd p'shift	40km/hr

Claas

Offset cab, selectable two/four-wheel steering

Scorpion 635 Varipower	3.50t	3.00t / 6.13m	std	V 160	136hp Deutz	3spd hydro	40km/hr
Scorpion 732 Varipower	3.20t	2.80t / 6.93m	std	V 160	136hp Deutz	3spd hydro	40km/hr
Scorpion 736 Varipower	3.60t	2.50t / 6.93m	std	V 160	136hp Deutz	3spd hydro	40km/hr
Scorpion 741 Varipower	4.10t	2.50t / 6.93m	std	V 160	136hp Deutz	3spd hydro	40km/hr
Scorpion 746 Varipower	4.60t	3.00t / 7.03m	std	V 200	156hp Deutz	3spd hydro	40km/hr
Scorpion 756 Varipower Plus	5.60t	3.50t / 7.03m	std	V 200	156hp Deutz	3spd hydro	40km/hr
Scorpion 1033 Varipower	3.30t	1.50t / 9.75m	std	V 160	136hp Deutz	3spd hydro	40km/hr

Note: Varipower Plus model has transmission with fixed displacement motor in addition to variable displacement pump.

Dieci

Central cab, articulated chassis steering

Agri Pivot T40	2.00t	1.25t / 4.30m	no	F 72	50hp Kubota	2spd hydro	22km/hr
Agri Pivot T50	2.20t	1.35t / 4.70m	opt	F 86	68hp Yanmar	2spd hydro	30km/hr
Agri Pivot T60	2.30t	1.40t / 5.00m	opt	F 98	75hp Yanmar	4spd hydro	40km/hr

Agri Pivot T70	3.00t	1.95t / 5.00m	opt	F 114	115hp Kubota	4spd hydro	40km/hr
Agri Pivot T80	3.50t	2.25t / 5.20m	opt	F 114	140hp FPT	4spd hydro	36km/hr
Offset cab, selectable two/four-wheel steering							
Mini Agri 25.6	2.50t	1.70t / 5.78m	opt	F 88	49hp Kubota	4spd hydro	26km/hr
Mini Agri 25.6	2.50t	1.70t / 5.78m	opt	F 88	75hp Kubota	4spd hydro	26km/hr
Agri Farmer 32.6	3.20t	2.60t / 6.00m	opt	F 110	101hp Kubota	4spd hydro	35km/hr
Agri Farmer 28.7	2.80t	2.00t / 6.35m	opt	F 110	101hp Kubota	4spd hydro	35km/hr
Agri Farmer 30.7	3.00t	2.00t / 6.35m	opt	F 110	101hp Kubota	4spd hydro	35km/hr
Agri Tech 35.7 VS	3.80t	2.50t / 7.00m	opt	F 110 or F 140	127hp FPT	4spd hydro	40km/hr
Agri Plus 40.7 PS6	4.00t	2.60t / 7.10m	opt	F 180	121hp FPT	6spd p'shift	40km/hr
Agri Plus 40.7 VS Evo 2	4.00t	2.60t / 7.10m	opt	F 210	143hp FPT	1spd x1 hydro	40km/hr
Agri Plus 40.7 VS Evo 2	4.00t	2.60t / 7.10m	opt	F 210	154hp FPT	1spd x1 hydro	40km/hr
Agri Star 40.7 Evo 2	4.00t	2.40t / 7.20m	opt	F 170	115hp Kubota	1spd x1 hydro	40km/hr
Agri Star 37.7	3.70t	3.50t / 7.35m	opt	F 110 or F 140	115hp Kubota	4spd hydro	40km/hr
Agri Max 65.8	6.50t	4.20t / 7.70m	opt	F 170	143hp FPT	4spd hydro	40km/hr
Agri Max 65.8	6.50t	4.20t / 7.70m	opt	F 170	154hp FPT	4spd hydro	40km/hr
Agri Max 65.8 VS Evo 2	6.50t	4.20t / 7.70m	opt	F 210	143hp FPT	1spd x1 hydro	40km/hr
Agri Max 65.8 VS Evo 2	6.50t	4.20t / 7.70m	opt	F 210	154hp FPT	1spd x1 hydro	40km/hr
Agri Max 45.8	4.50t	2.70t / 7.90m	opt	F 110 or F 140	115hp Kubota	4spd hydro	40km/hr
Agri Max 60.9	6.00t	3.50t / 8.60m	opt	F 170	143hp FPT	4spd hydro	40km/hr
Agri Max 60.9	6.00t	3.50t / 8.60m	opt	F 170	154hp FPT	4spd hydro	40km/hr
Agri Max 60.9 VS Evo 2	6.00t	3.50t / 8.60m	opt	F 210	143hp FPT	1spd x1 hydro	40km/hr
Agri Max 60.9 VS Evo 2	6.00t	3.50t / 8.60m	opt	F 210	154hp FPT	1spd x1 hydro	40km/hr
Agri Farmer 28.9	2.80t	1.20t / 8.70m	opt	F 110	101hp Kubota	4spd hydro	35km/hr
Agri Farmer 30.9	3.00t	1.20t / 8.70m	opt	F 110	101hp Kubota	4spd hydro	35km/hr
Agri Tech 32.9 VS	3.20t	2.00t / 9.00m	opt	F 110 or F 140	127hp FPT	4spd hydro	40km/hr
Agri Plus 38.9 VS Evo 2	3.80t	1.90t / 9.00m	opt	F 210	143hp FPT	1spd x1 hydro	40km/hr
Agri Plus 38.9 VS Evo 2	3.80t	1.90t / 9.00m	opt	F 210	154hp FPT	1spd x1 hydro	40km/hr
Agri Star 38.10 Evo 2	3.80t	0.75t / 9.60m	opt	F 170	115hp Kubota	1spd x1 hydro	40km/hr
Agri Max 75.10	7.00t	4.00t / 9.65m	opt	F 170	143hp FPT	4spd hydro	40km/hr
Agri Max 75.10	7.00t	4.00t / 9.65m	opt	F 170	154hp FPT	4spd hydro	40km/hr

Note: VS models have four-mode electronic management of single variable output pump hydrostatic drive; Agri Tech equipped with 4000kg lift three-point linkage, pto and up to three remote valves; multi-mode hydro CVT drive.

Faresin

Offset cab, selectable two/four-wheel steering

6.26	2.60t	1.75t / 5.70m	opt	F 73	70hp Yanmar	1spd hydro	27km/hr
6.30 Compact Agritop	3.00t	2.50t / 6.00m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
6.30 Compact GLS	3.00t	2.50t / 6.00m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
6.30 Compact VPS	3.00t	2.50t / 6.00m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
7.30 Compact Agritop	3.00t	2.00t / 7.10m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
7.30 Compact GLS	3.00t	2.00t / 7.10m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
7.30 Compact VPS	3.00t	2.00t / 7.10m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
7.30 Agritop	3.00t	2.00t / 7.10m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
7.30 GLS	3.00t	2.00t / 7.10m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
7.30 VPSe	3.00t	2.00t / 7.10m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
7.35 Agritop	3.50t	2.50t / 7.10m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
7.35 GLS	3.50t	2.50t / 7.10m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
7.35 VPSe	3.50t	2.50t / 7.10m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
7.45 Agritop	4.50t	3.00t / 7.10m	opt	F 120	100hp Deutz	4spd hydro	40km/hr

Manitou

7.45 GLS	4.50t	3.00t / 7.10m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
7.45 VPSe	4.50t	3.00t / 7.10m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
7.30 Compact VPS	3.00t	2.00t / 7.10m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
8.40 Agritop	4.00t	2.00t / 8.00m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
8.40 GLS	4.00t	2.00t / 8.00m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
8.40 VPSe	4.00t	2.00t / 8.00m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
8.40 VPSe TOP	4.00t	2.00t / 8.00m	opt	V 185	156hp Deutz	1spd x2 hydro	40km/hr
9.60 Heavy Duty GLS	5.50t	3.00t / 8.80m	opt	V 145	120hp Deutz	4spd hydro	40km/hr
9.60 Heavy Duty VPSe	5.50t	3.00t / 8.80m	opt	V 145	120hp Deutz	1spd x2 hydro	40km/hr
9.70 Heavy Duty GLS	7.00t	4.00t / 8.80m	opt	V 152	120hp Deutz	4spd hydro	40km/hr
9.70 Heavy Duty VPSe	7.00t	4.00t / 8.80m	opt	V 152	120hp Deutz	1spd x2 hydro	40km/hr
9.30 Compact Agritop	3.00t	1.20t / 8.90m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
9.30 Compact GLS	3.00t	1.20t / 8.90m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
9.30 Compact VPS	3.00t	1.20t / 8.90m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
9.30 Compact VPS	3.00t	1.20t / 8.90m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr
9.30 Agritop	3.00t	2.00t / 9.00m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
9.30 GLS	3.00t	2.00t / 9.00m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
9.30 VPSe TOP	3.00t	2.00t / 9.00m	opt	V 185	122hp Deutz	1spd x2 hydro	40km/hr
10.65 Heavy Duty GLS	6.50t	2.50t / 9.50m	opt	V 145	120hp Deutz	4spd hydro	40km/hr
10.65 Heavy Duty VPSe	6.50t	2.50t / 9.5m	opt	V 145	120hp Deutz	1spd x2 hydro	40km/hr
11.35 Agritop	3.50t	1.50t / 10.0m	opt	F 120	100hp Deutz	4spd hydro	40km/hr
11.35 GLS	3.50t	1.50t / 10.0m	opt	V 152	122hp Deutz	4spd hydro	40km/hr
11.35 VPSe	3.50t	1.50t / 10.0m	opt	V 152	122hp Deutz	1spd x2 hydro	40km/hr

Note: Agritop and GLS models have a two-speed gearbox and two-range single pump hydrostatic drive; GLS Heavy Duty models have separate engine and ground speed control; VPS models have twin hydraulic motor hydrostatic drive with independent engine and ground speed control available using 'creeper' function; VPSe models have twin hydraulic motor hydrostatic drive and automatic two-speed gearbox with independent engine and ground speed control. Compact GLS and VPS models can be equipped with 3000kg rear linkage with float, and two-speed mechanical rear pto.

JCB
Central cab, skid steering

Teleskid 3TS-8W	0.60t	0.60t / 4.05m	no	F 90	74hp JCB	2spd hydro	20km/hr
Teleskid 3TS-8T	0.70t	0.73t / 4.03m	no	F 90-125	74hp JCB	2spd hydro	13km/hr

Central cab, articulated chassis steering

TeleMaster TM180	1.80t	1.80t / 4.50m	no	F 64	64hp JCB Kohler	2spd hydro	20km/hr
TeleMaster TM220	2.20t	2.20t / 4.60m	no	F 89	74hp JCB Kohler	2/3spd hydro	20km/hr
TeleMaster TM220 HS	2.20t	2.20t / 4.60m	no	F 89	74hp JCB Kohler	2/3spd hydro	40km/hr
TeleMaster TM320	3.20t	3.20t / 5.20m	std	V 140	125hp JCB	6spd p'shift	40km/hr
TeleMaster TM320S	3.20t	3.20t / 5.20m	std	V 160	145hp JCB	6spd p'shift	40km/hr
TeleMaster TM420	4.10t	4.10t / 5.45m	std	V 160	145hp JCB	6spd p'shift	40km/hr

Central cab, permanent four-wheel steering

Loadall 516-40 Agri	1.60t	1.60t / 4.04m	no	F 56	47hp Kohler	2/3spd hydro	26km/hr
---------------------	-------	---------------	----	------	-------------	--------------	---------

Offset cab, selectable two/four-wheel steering

Loadall 520-40 Agri	2.00t	2.00t / 4.03m	no	F 60	49hp Perkins	2spd hydro	20km/hr
Loadall 526-56 Agri Plus	2.60t	2.60t / 5.60m	opt	F 80	109hp JCB	4spd p'shift	33km/hr
Loadall 527-58 Agri Plus	2.70t	2.70t / 5.80m	opt	F 126	109hp JCB	2spd hydro	33km/hr
Loadall 525-60 Agri	2.50t	1.75t / 6.00m	opt	F 80	74hp JCB Kohler	2spd hydro	25km/hr
Loadall 525-60 Agri Plus	2.50t	1.75t / 6.00m	opt	F 90	74hp JCB Kohler	2spd hydro	30km/hr
Loadall 536-60 Agri	3.60t	3.60t / 6.20m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 536-60 Agri Torquelock 4	3.60t	3.60t / 6.20m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 536-60 Agri Plus	3.60t	3.60t / 6.20m	opt	V 140	125hp JCB	4spd p'shift	33km/hr
Loadall 536-60 Agri Plus	3.60t	3.60t / 6.20m	opt	V 140	145hp JCB	4spd p'shift	33km/hr

JCB

Loadall 536-60 Agri Super	3.60t	3.60t / 6.20m	std	V 140	125hp JCB	6spd p'shift	40km/hr
Loadall 536-60 Agri Super	3.60t	3.60t / 6.20m	std	V 140	145hp JCB	6spd p'shift	40km/hr
Loadall 536-60 Agri Pro DualTech VT	3.60t	3.60t / 6.20m	std	V 140	145hp JCB	1spd hydro + 3spd p'shift*	40km/hr
Loadall 531-70 Agri	3.10t	2.40t / 7.00m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 531-70 Agri Torquelock 4	3.10t	2.40t / 7.00m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 531-70 Agri Plus	3.10t	2.40t / 7.00m	opt	V 140	125hp JCB	4spd p'shift	33km/hr
Loadall 531-70 Agri Plus	3.10t	2.40t / 7.00m	opt	V 140	145hp JCB	4spd p'shift	33km/hr
Loadall 531-70 Agri Super	3.10t	2.40t / 7.00m	std	V 140	125hp JCB	6spd p'shift	40km/hr
Loadall 531-70 Agri Super	3.10t	2.40t / 7.00m	std	V 140	145hp JCB	6spd p'shift	40km/hr
Loadall 531-70 Agri Pro DualTech VT	3.10t	2.40t / 7.00m	std	V 140	145hp JCB	1spd hydro + 3spd p'shift*	40km/hr
Loadall 536-70 Agri	3.60t	2.25t / 7.00m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 536-70 Agri Torquelock 4	3.60t	2.25t / 7.00m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 536-70 Agri Plus	3.60t	2.25t / 7.00m	opt	V 140	125hp JCB	4spd p'shift	33km/hr
Loadall 536-70 Agri Plus	3.60t	2.25t / 7.00m	opt	V 140	145hp JCB	4spd p'shift	33km/hr
Loadall 536-70 Agri Super	3.60t	2.25t / 7.00m	std	V 140	125hp JCB	6spd p'shift	40km/hr
Loadall 536-70 Agri Super	3.60t	2.25t / 7.00m	std	V 140	145hp JCB	6spd p'shift	40km/hr
Loadall 536-70 Agri Pro DualTech VT	3.60t	2.25t / 7.00m	std	V 140	125hp JCB	6spd p'shift	40km/hr
Loadall 541-70 Agri	4.10t	2.25t / 7.00m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 541-70 Agri Torquelock 4	4.10t	2.25t / 7.00m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 541-70 Agri Plus	4.10t	2.25t / 7.00m	opt	V 140	125hp JCB	4spd p'shift	33km/hr
Loadall 541-70 Agri Plus	4.10t	2.25t / 7.00m	opt	V 140	145hp JCB	4spd p'shift	33km/hr
Loadall 541-70 Agri Super	4.10t	2.25t / 7.00m	std	V 140	125hp JCB	6spd p'shift	40km/hr
Loadall 541-70 Agri Super	4.10t	2.25t / 7.00m	std	V 140	145hp JCB	6spd p'shift	40km/hr
Loadall 541-70 Agri Pro DualTech VT	4.10t	2.25t / 7.00m	std	V 140	145hp JCB	1spd hydro + 3spd p'shift*	40km/hr
Loadall 560-80 Agri Plus	6.00t	3.00t / 8.10m	std	V 140	125hp JCB	4spd p'shift	33km/hr
Loadall 560-80 Agri Plus	6.00t	3.00t / 8.10m	std	V 140	145hp JCB	4spd p'shift	33km/hr
Loadall 560-80 Agri Super	6.00t	3.00t / 8.10m	std	V 140	125hp JCB	4spd p'shift	33km/hr
Loadall 560-80 Agri Super	6.00t	3.00t / 8.10m	std	V 140	145hp JCB	4spd p'shift	33km/hr
Loadall 560-80 Agri Pro DualTech VT	6.00t	3.00t / 8.10m	std	V 140	145hp JCB	1spd hydro + 3spd p'shift*	40km/hr
Loadall 535-95 Agri	3.50t	1.60t / 9.50m	opt	V 140	109hp JCB	4spd p'shift	33km/hr
Loadall 535-95 Agri Plus	3.50t	1.60t / 9.50m	opt	V 140	125hp JCB	4spd p'shift	33km/hr
Loadall 535-95 Agri Plus	3.50t	1.60t / 9.50m	opt	V 140	145hp JCB	4spd p'shift	33km/hr
Loadall 535-95 Agri Super	3.50t	1.60t / 9.50m	std	V 140	125hp JCB	6spd p'shift	40km/hr
Loadall 535-95 Agri Super	3.50t	1.60t / 9.50m	std	V 140	145hp JCB	6spd p'shift	40km/hr
Loadall 535-95 Agri Pro DualTech VT	3.50t	1.60t / 9.50m	std	V 140	145hp JCB	1spd hydro + 3spd p'shift*	40km/hr

Note: Optional separate engine speed and ground speed control available on 516-40 and 525-60; Agri Pro models have separate engine and ground speed control as standard; * direct drive (no torque converter). Plus - optional seat-mounted servo joystick; Super - standard seat-mounted servo joystick.

Knikmops

Central cab, articulated chassis steering

KM100 Tele	0.23t	0.23t / 2.96m	opt	F 33	25hp Kubota	1spd hydro	18km/hr
KM120 Tele	0.52t	0.38t / 3.20m	opt	F 33	25hp Kubota	1spd hydro	18km/hr
KM130 Tele	0.52t	0.38t / 3.20m	opt	F 42	36hp Kubota	1spd hydro	20km/hr
KM170 Tele	0.82t	0.61t / 3.31m	opt	F 42	36hp Kubota	1spd hydro	18km/hr
KM180 Tele	0.82t	0.61t / 3.31m	opt	F 50	44hp Kubota	1spd hydro	20km/hr
KM250 Tele	0.95t	0.71t / 3.55m	opt	F 62	49hp Kubota	2spd hydro	20km/hr

Note: All models have hydrostatic wheel motor drive.

AGCO

Kramer							
Central cab, articulated chassis steering							
KL25.5T	1.65t	1.65t / 4.00m	opt	F 70	47hp Yanmar	2spd hydro	27km/hr
KL30.5T	2.00t	2.00t / 4.48m	opt	F 70	75hp Kohler	2spd hydro	30km/hr
KL30.8T	2.00t	2.00t / 4.48m	opt	F 84	75hp Deutz	2spd hydro	30/40km/hr
KL35.8T	2.30t	2.30t / 4.50m	opt	F 84	100hp Deutz	2spd hydro	30/40km/hr
Offset cab, permanent four-wheel steering							
KT804	0.80t	0.80t / 4.00m	no	F 33	26hp Yanmar	2spd hydro	17km/hr
KT1245	1.20t	1.20t / 4.30m	no	F 42 or F 75	40hp Yanmar	2spd hydro	20km/hr
Offset cab, selectable two/four-wheel steering							
KT2205	2.20t	1.70t / 5.18m	opt	F 70 or F 106	49hp Perkins	2spd hydro	20km/hr
KT276 Hydrostat	2.70t	2.50t / 5.73m	std	F 90	75hp Kohler	2spd hydro	30km/hr
KT306 Hydrostat	3.00t	2.50t / 6.15m	opt	F 100	136hp Deutz	3spd hydro	30km/hr
KT356 Ecospeed	3.50t	3.00t / 6.15m	std	V 140	136hp Deutz	3spd hydro	40km/hr
KT307 Hydrostat	3.00t	2.00t / 7.00m	opt	F 100	136hp Deutz	3spd hydro	30km/hr
KT357 Ecospeed	3.50t	2.20t / 7.00m	std	V 140	136hp Deutz	3spd hydro	40km/hr
KT447 Ecospeed	4.30t	3.30t / 7.01m	std	V 140	122hp Deutz	3spd hydro	40km/hr
KT507 Ecospeed Pro	4.80t	3.50t / 7.01m	std	V 140	136hp Deutz	3spd hydro	40km/hr
KT557 Ecospeed Pro	5.50t	4.00t / 7.01m	std	V 187	156hp Deutz	3spd hydro	40km/hr
KT559 Ecospeed Pro	5.50t	5.50t / 8.75m	std	V 187	156hp Deutz	3spd hydro	40km/hr

Note: Ecospeed Pro models have transmission with fixed displacement motor in addition to variable displacement pump.

Manitou							
Central cab, articulated chassis steering							
MLA-T 533-145 V Classic	3.30t	3.30t / 5.20m	opt	V 158	143hp Deutz	1spd x2 hydro	40km/hr
MLA-T 533-145 V Premium	3.30t	3.30t / 5.20m	opt	V 158	143hp Deutz	1spd x2 hydro	40km/hr
MLA-T 533-145 V Elite	3.30t	3.30t / 5.20m	std	V 158	143hp Deutz	1spd x2 hydro	40km/hr
Offset cab, selectable two/four-wheel steering							
MLT 625 75 H Classic	2.50t	2.00t / 5.90m	opt	F 90	75hp Kubota	2spd hydro	30km/hr
MLT 625-75 H Premium	2.50t	2.00t / 5.90m	opt	F 90	75hp Kubota	2spd hydro	30km/hr
MLT 625-75 H Elite	2.50t	2.00t / 5.90m	std	F 90	75hp Kubota	2spd hydro	30km/hr
MLT 630-105 VCP Classic	3.00t	2.70t / 6.00m	opt	F 104	101hp Deutz	2spd hydro	30km/hr
MLT 630-105 VCP Premium	3.00t	2.70t / 6.00m	opt	F 104	101hp Deutz	2spd hydro	30km/hr
MLT 630-105 VCP Elite	3.00t	2.70t / 6.00m	std	F 104	101hp Deutz	2spd hydro	30km/hr
MLT 635-130 PS+ Classic	3.50t	3.50t / 6.08m	opt	V 150	129hp Deutz	6spd p'shift	40km/hr
MLT 635-130 PS+ Premium	3.50t	3.50t / 6.08m	opt	V 150	129hp Deutz	6spd p'shift	40km/hr
MLT 635-130 PS+ Elite	3.50t	3.50t / 6.08m	std	V 150	129hp Deutz	6spd p'shift	40km/hr
MLT 635-140 V+ Classic	3.50t	3.50t / 6.08m	opt	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 635-140 V+ Premium	3.50t	3.50t / 6.08m	opt	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 635-140 V+ Elite	3.50t	3.50t / 6.08m	std	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 630-105 V Classic	3.00t	2.70t / 6.10m	opt	F 104	101hp Deutz	2spd hydro	40km/hr
MLT 630-105 V Premium	3.00t	2.70t / 6.10m	opt	F 104	101hp Deutz	2spd hydro	40km/hr
MLT 630-105 V Elite	3.00t	2.70t / 6.10m	std	F 104	101hp Deutz	2spd hydro	40km/hr
MLT 630-105 Classic	3.00t	2.70t / 6.10m	opt	F 104	101hp Deutz	4spd manual	32km/hr
MLT 630-105 Premium	3.00t	2.70t / 6.10m	opt	F 104	101hp Deutz	4spd manual	32km/hr
MLT 630-105 Elite	3.00t	2.70t / 6.10m	std	F 104	101hp Deutz	4spd manual	32km/hr
MLT 730-115 VCP Classic	3.00t	2.00t / 6.85m	opt	F 104	116hp Deutz	2spd hydro	32km/hr
MLT 730-115 VCP Premium	3.00t	2.00t / 6.85m	opt	F 104	116hp Deutz	2spd hydro	32km/hr
MLT 730-115 VCP Elite	3.00t	2.00t / 6.85m	std	F 104	116hp Deutz	2spd hydro	32km/hr
MLT 733-115 Classic	3.30t	3.30t / 6.90m	opt	F 104	116hp Deutz	4spd manual	32km/hr

MLT 733-115 Premium	3.30t	3.30t / 6.90m	opt	F 104	116hp Deutz	4spd manual	32km/hr
MLT 733-115 LSU Classic	3.30t	3.30t / 6.90m	opt	V 150	116hp Deutz	4spd manual	32km/hr
MLT 733-115 LSU Premium	3.30t	3.30t / 6.90m	opt	V 150	116hp Deutz	4spd manual	32km/hr
MLT 737-130 PS+ Classic	3.70t	2.70t / 6.90m	opt	V 150	129hp Deutz	6spd p'shift	40km/hr
MLT 737-130 PS+ Premium	3.70t	2.70t / 6.90m	opt	V 150	129hp Deutz	6spd p'shift	40km/hr
MLT 737-130 PS+ Elite	3.70t	2.70t / 6.90m	std	V 150	129hp Deutz	6spd p'shift	40km/hr
MLT 741-140 V+ Classic	4.10t	2.70t / 6.90m	opt	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 741-140 V+ Premium	4.10t	2.70t / 6.90m	opt	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 741-140 V+ Elite	4.10t	2.70t / 6.90m	std	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 730-115 V Classic	3.00t	2.00t / 6.95m	opt	F 104	116hp Deutz	2spd hydro	36km/hr
MLT 730-115 V Premium	3.00t	2.00t / 6.95m	opt	F 104	116hp Deutz	2spd hydro	36km/hr
MLT 730-115 V Elite	3.00t	2.00t / 6.95m	std	F 104	116hp Deutz	2spd hydro	36km/hr
MLT 840-145 PS Classic	4.00t	2.00t / 7.55m	opt	V 200	141hp Deere	5spd p'shift	40km/hr
MLT 840-145 PS Premium	4.00t	2.00t / 7.55m	opt	V 200	141hp Deere	5spd p'shift	40km/hr
MLT 840-145 PS Elite	4.00t	2.00t / 7.55m	std	V 200	141hp Deere	5spd p'shift	40km/hr
MLT 845-120 LSU Classic	4.50t	2.00t / 7.55m	opt	V 150	122hp Deutz	4spd manual	40km/hr
MLT 845-120 LSU Premium	4.50t	2.00t / 7.55m	opt	V 151	122hp Deutz	4spd manual	40km/hr
MLT 845-120 LSU Elite	4.50t	2.00t / 7.55m	std	V 152	122hp Deutz	4spd manual	40km/hr
MLT 940-140 V+ Classic	4.00t	1.50t / 9.00m	opt	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 940-140 V+ Premium	4.00t	1.50t / 9.00m	opt	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 940-140 V+ Elite	4.00t	1.50t / 9.00m	std	V 170	136hp Deutz	1spd x2 hydro	40km/hr
MLT 960 Classic	6.00t	3.50t / 9.00m	opt	V 180	141hp Deere	1spd x2 hydro	40km/hr

Dieci

MLT 960 Premium	6.00t	3.50t / 9.00m	opt	V 180	141hp Deere	1spd x2 hydro	40km/hr
MLT 960 Elite	6.00t	3.50t / 9.00m	std	V 180	141hp Deere	1spd x2 hydro	40km/hr
MLT 1040-145 PS L Classic *	4.00t	2.50t / 9.60m	opt	V 200	141hp Deere	5spd p'shift	40km/hr
MLT 1040-145 PS L Premium *	4.00t	2.50t / 9.60m	opt	V 200	141hp Deere	5spd p'shift	40km/hr
MLT 1040-145 PS L Elite *	4.00t	2.50t / 9.60m	std	V 200	141hp Deere	5spd p'shift	40km/hr

Note: Models with twin pump hydrostatic drive have independent engine and ground speed control. Elite and Premium versions have air conditioning and easy connect system as standard. * equipped with self-levelling system.

Massey Ferguson

Offset cab, selectable two/four-wheel steering

TH.6030	3.00t	2.50t / 5.89m	std	F 100	100hp Doosan	2spd hydro	40km/hr
TH.6534	3.40t	3.40t / 6.41m	std	V 190	130hp Doosan	4spd hydro	40km/hr
TH.7030	3.00t	2.00t / 6.70m	std	F 100	100hp Doosan	2spd hydro	40km/hr
TH.7035	3.50t	3.50t / 6.97m	std	F 100	100hp Doosan	4spd hydro	40km/hr
TH.7038	3.80t	3.50t / 6.97m	std	V 190	130hp Doosan	4spd hydro	40km/hr

Note: All models have selectable independent ground/engine speed control; four-speed transmissions have two mechanical gears and two hydrostatic ranges.

Merlo

Offset cab, selectable two/four-wheel steering

P27.6 Plus	2.70t	1.75t / 6.00m	opt	F 94	75hp Kubota	1spd hydro	50km/hr
TF33.7-115	3.30t	2.60t / 6.70m	opt	V 125	115hp Deutz	2spd hydro	40km/hr
TF33.7-115L	3.30t	2.60t / 6.70m	opt	V 125	115hp Deutz	2spd hydro	40km/hr
TF35.7-115	3.50t	3.50t / 6.70m	opt	V 125	115hp Deutz	2spd hydro	40km/hr
TF35.7CS-115	3.50t	3.50t / 6.70m	opt	V 125	115hp Deutz	2spd hydro	40km/hr
Multifarmer MF40.7CS-170 CVTronic	4.00t	4.00t / 6.80m	std	V 150	170hp FPT	1spd x2 hydro	40km/hr
TF42.7-140	4.20t	3.50t / 7.10m	opt	V 150	140hp Deutz	2spd hydro	40km/hr
TF42.7CS-140	4.20t	3.50t / 7.10m	opt	V 150	140hp Deutz	2spd hydro	40km/hr
TF42.7CS-140 CVTronic	4.20t	3.50t / 7.10m	opt	V 150	140hp Deutz	1spd x2 hydro	40km/hr
TF50.8 T CS-170 CVTronic	5.00t	5.00t / 7.80m	opt	V 150	170hp FPT	1spd x2 hydro	40km/hr
Multifarmer MF40.9CS-170 CVTronic	4.00t	4.00t / 8.80m	std	V 150	170hp FPT	1spd x2 hydro	40km/hr
TF38.10-140	3.80t	1.50t / 9.60m	opt	V 150	140hp Deutz	2spd hydro	40km/hr
TF38.10CS-140	3.80t	1.50t / 9.60m	opt	V 150	140hp Deutz	2spd hydro	40km/hr
TF38.10CS-140 CVTronic	3.80t	1.50t / 9.60m	opt	V 150	140hp Deutz	1spd x2 hydro	40km/hr
TF38.10 TT CS-140 CVTronic	3.80t	1.50t / 9.60m	opt	V 150	140hp Deutz	1spd x2 hydro	40km/hr
Panoramic P60.10 TT	6.00t	4.00t / 9.60m	opt	V 108	101hp Deutz	2spd hydro	40km/hr
Panoramic P72.10 TT	7.20t	4.00t / 9.60m	opt	V 108	101hp Deutz	2spd hydro	40km/hr
TF45.11 T CS-170 CVTronic	4.50t	3.50t / 10.6m	opt	V 150	170hp FPT	1spd x2 hydro	40km/hr

Note: L - low-mounted cab; CS - cab suspension standard; TT - levelling and sideshift front axle; CVTronic - twin hydraulic motor transmission. Multifarmer models are equipped with integral 7000kg rear linkage, two-speed mechanical rear pto and trailer braking system. Separate ground and engine speed control optional or standard on all models; EPD Plus provides engine speed control according to joystick movement.

MultiOne

Central cab, articulated chassis steering

4.2	1.00t	0.70t / 2.75m	no	F 31	20hp Kubota	1spd hydro	14km/hr
5.3	1.14t	0.64t / 2.75m	no	F 42	28hp Yanmar	1spd hydro	14km/hr
7.2	1.55t	1.24t / 2.90m	no	F 68	28hp Yanmar	1spd hydro	11km/hr
7.3	1.55t	1.24t / 2.90m	no	F 68	35hp Yanmar	1spd hydro	13/15km/hr
6.3	1.20t	0.96t / 2.92m	no	F 46	28hp Yanmar	1spd hydro	13/15km/hr
8.4+	1.60t	1.28t / 2.98m	no	F 72	40hp Yanmar	1spd hydro	13/15km/hr
9.5	2.6t	2.08t / 3.21m	no	F 85	50hp Yanmar	2spd hydro	25km/hr
10.8	2.7t	2.16t / 3.21m	no	F 95	72hp Yanmar	2spd hydro	40km/hr

NC Engineering

Central cab, articulated chassis steering

FH225	2.40t	2.40t / 4.69m	opt	V 103	75hp Deutz	6spd p'shift	29km/hr
-------	-------	---------------	-----	-------	------------	--------------	---------

New Holland

Offset cab, selectable two/four-wheel steering

LM5.25	2.50t	2.50t / 5.78m	opt	F 80	74hp Kubota	1spd hydro	26km/hr
LM6.32	3.20t	3.20t / 6.10m	std	F 120	133hp FPT	4spd p'shift	40km/hr
LM6.35 Elite	3.50t	3.50t / 6.10m	std	V 140	146hp FPT	6spd p'shift	40km/hr
LM7.35	3.50t	3.50t / 7.00m	std	F 120	133hp FPT	4spd p'shift	40km/hr
LM7.42 Elite	4.20t	4.20t / 7.00m	std	V 140	146hp FPT	6spd p'shift	40km/hr
LM9.35	3.50t	2.50t / 9.10m	std	F 120	133hp FPT	4spd p'shift	40km/hr

Note: Elite specification includes seat-mounted electronic joystick and reach-adjustable (in addition to tilt) steering wheel.

Norcar

Central cab, articulated chassis steering

765	1.20t	1.20t / 2.90m	no	F 50	36hp Kubota	1spd hydro	15km/hr
a6020	0.96t	0.96t / 3.01m	no	F 28	20hp Kubota	1spd hydro	17km/hr
a6026	0.96t	0.96t / 3.01m	no	F 24	26hp Kubota	1spd hydro	15km/hr
a6226	1.15t	0.96t / 3.01m	no	F 18+24	26hp Kubota	2spd hydro	19km/hr
a7236	1.50t	1.10t / 3.54m	no	F 24+33	36hp Kubota	2spd hydro	20km/hr
a7545	1.50t	1.10t / 3.54m	no	F 33+33	45hp Kubota	2spd hydro	20km/hr
a7545 4 Track	1.65t	1.20t / 3.64m	no	F 33+33	45hp Kubota	2spd hydro	10km/hr

Note: Model a7545 4 Track runs on individual track assemblies.

Pichon

Central cab, articulated chassis steering

Series 45.60	2.00t	1.60t / 4.5m	opt	F 96	60hp Deutz	2spd hydro	25km/hr
--------------	-------	--------------	-----	------	------------	------------	---------

Claas

Series 45.75	2.00t	1.60t / 4.5m	opt	F 96	75hp Deutz	2spd hydro	25km/hr
Q Loader							
Central cab, articulated chassis steering							
Q27 Telescopic	1.10t	1.10t / 3.43m	no	F 42	37hp Yanmar	2spd hydro	na
Schäffer							
Central cab, articulated chassis steering							
2345 T	1.90t	1.65t / 3.75m	opt	F 42	45hp Kubota	2spd hydro	20km/hr
2345 T SLT	1.90t	1.65t / 3.75m	opt	F 42	45hp Kubota	2spd hydro	20km/hr
3550 T	1.95t	1.70t / 3.85m	opt	F 52	50hp Kubota	2spd hydro	20/28km/hr
3550 T SLT	1.95t	1.70t / 3.85m	opt	F 52	50hp Kubota	2spd hydro	20/28km/hr
5650 T	2.40t	1.90t / 4.25m	opt	F 64	50hp Kubota	2spd hydro	20km/hr
5680 T	2.40t	1.90t / 4.70m	opt	F 72	75hp Deutz	2spd hydro	20/30km/hr
6680 T	3.10t	2.70t / 4.90m	opt	F 64	75hp Deutz	2spd hydro	20/35km/hr
8620 T	4.20t	3.80t / 5.20m	opt	V 105	102hp Deutz	2spd hydro	20/40km/hr
8620 T	4.20t	3.80t / 5.20m	std*	V 105	122hp Deutz	2spd hydro	20/40km/hr
9640 T	4.20t	4.10t / 5.40m	opt	V 145	136hp Deutz	2spd hydro	20/40km/hr
9660 T	5.30t	4.80t / 6.10m	opt	V 220	157hp Deutz	2spd hydro	30/40km/hr
<i>Note: SLT versions of 2345T and 3550T have lower overall height; * standard with 40km/hr transmission.</i>							
Tobroco							
Central cab, articulated chassis steering							
Giant D204SW Tele	1.00t	0.75t / 2.80m	no	F 33	20hp Kubota	1spd hydro	15km/hr
Giant D254SW Tele	1.00t	0.75t / 2.80m	no	F 33	25hp Kubota	1spd hydro	15km/hr
Giant V4502T Tele	2.00t	1.50t / 4.30m	opt	F 60	45hp Kubota	2spd hydro	25km/hr
Giant V5003T Tele	2.00t	1.50t / 4.30m	opt	F 66	50hp Kubota	2spd hydro	25km/hr
Giant V501 Tele	2.00t	1.40t / 5.10m	opt	F 80	50hp Deutz	2spd hydro	25km/hr
Giant V761T Tele	2.80t	1.40t / 5.10m	opt	F 80, V105 or V 145	76hp Deutz	2spd hydro	25/35km/hr
Offset cab, selectable two/four-wheel steering							
Giant 3648 Tendo	1.40t	0.80t / 4.80m	opt	F 52	36hp Kubota	2spd hydro	25km/hr
Giant 4648 Tendo HD	1.40t	0.80t / 4.80m	opt	F 52	45hp Kubota	2spd hydro	25km/hr
Weidemann							
Central cab, articulated chassis steering							
2070 CX50 LP T	1.80t	1.00t / 4.30m	opt	F 49	49hp Perkins	2spd hydro	20/28km/hr
2070 CX80 LP T	1.90t	1.10t / 4.30m	opt	F 52	75hp Deutz	2spd hydro	20/28km/hr
2080 T	2.20t	1.50t / 4.30m	opt	F 56, 63 or 83	50hp Perkins	2spd hydro	20/28km/hr
2080 T	2.20t	1.50t / 4.30m	opt	F 56, 63 or 84	60hp Perkins	2spd hydro	20/28km/hr
2080 T	2.60t	1.60t / 4.30m	opt	F 56, 63 or 85	75hp Deutz	2spd hydro	20/28km/hr
3080 LP T	2.20t	1.20t / 5.00m	std	F 73 or F 103	75hp Deutz	2spd hydro	20/30km/hr
3080 T	2.60t	1.50t / 5.00m	std	F 73 or F 103	75hp Deutz	2spd hydro	20/30km/hr
4080 LP T	3.10t	1.80t / 5.00m	std	F 73 or F 83	75hp Deutz	2spd hydro	20/30km/hr
4080 T	3.10t	1.80t / 5.00m	std	F 100 or V 150	102hp Perkins	2spd hydro	30/40km/hr
5080 T	4.10t	2.50t / 5.00m	std	F 100 or V 150	122hp Perkins	2spd hydro	30/40km/hr
9080 T	6.50t	na / 5.48m	std	V 150 or V 180	136hp Deutz	3spd hydro	30/40km/hr
9080 T	6.50t	na / 5.48m	std	V 150 or V 180	156hp Deutz	3spd hydro	30/40km/hr
Offset cab, permanent four-wheel steering							
T4108	0.80t	0.80t / 4.10m	no	F 33	26hp Yanmar	2spd hydro	17km/hr
T4512	1.20t	1.10t / 4.50m	no	F 40 or F 70	40hp Yanmar	2spd hydro	20km/hr
T5522	2.20t	1.70t / 5.50m	std	F 70 or F 106	49hp Perkins	2spd hydro	20/30km/hr
T5522	2.20t	1.70t / 5.50m	std	F 70 or F 106	68hp Perkins	2spd hydro	20/30km/hr
T6027	2.70t	2.70t / 6.00m	std	F 90	75hp Kohler	3spd hydro	20/30km/hr